

60 & 80 600/800 kg



Call for Yanmar solutions













TECHNICAL SPECIFICATIONS

60/80 Series

60 serie



80 serie



COMPACT AND POWERFUL

The new line of micro- and mini-dumpers « Powered by Yanmar» ideally suited for landscaping and horticultural applications as well as construction sites.

The 60 series has an operating load of 600 kg and is available in two versions: Standard (415 kg) and High-Tip (535 kg). The 80 series, with its operating load of 800 kg, is also available in Standard (500 kg) and High-Tip (600 kg) and can be provided with an optional self-loading system (Standard and High-Tip). The High-Tip models have a discharge height of up to 1,675 mm and are able to tip their payload into most skips, over garden walls and fences and on to raised working levels.

All these models combine high performance, absolute reliability and great compactness. The dimensions of the 60 and 80 series allow them to work in very confined areas where their width (respectively 695 and 800 mm in standard version) can be a real operating bonus. They are also equipped with a very strong tracked undercarriage able to climb stairs or to

operate on difficult soft ground or through snow. The rocking roller design smoothes the passage of the machine over rough areas allowing the load to remain securely in the skip. The 60 & 80 are built to transport all types of building materials and are also suited for the disposal of soil, aggregates and turf.

Micro- and mini-dumpers « Powered by Yanmar » are powered by new Yanmar diesel engines (LA70 7.5hp and LN 100 AE 10hp). They are equipped with an excellent hydrostatic transmission based on pumps with axial pistons and variable flow. This system can provide the specific combination of speed and power needed by the operator. The hydraulic systems for the services and for transmission are separated thus enabling to use the loading functions while travelling. 60 series and 80 series have a top travel speed of 3.6 km/h and 4.8 km/h. The engine hood is solidly attached to the undercarriage and provides optimum servicing and maintenance access through its back cover. The ergonomically designed control panel includes all the switches and levers needed to operate the dumpers.

			60 serie / 600 kg	80 serie / 800 kg
Engine			Yanmar LA70 7.5 hp (Diesel)	Yanmar LN 100 AE 10hp (Diesel)
Transmission	Туре		Hydrostatic	Hydrostatic
	Hydraulic pump		3 x gear pump	2 x variable displ. pumps
	Flow		2 x 12 l/mn + 1 x 14 l/mn	2 x 32.4 l/mn
	Hydraulic motor		2 x orbital	2 x orbital
	Brake Parking			Mechanical
Hydraulic System	Hydraulic pump		Gear pump	Gear pump
	Flow		1 x 14 l/mn	1 x 13.5 l/mn
	High-flow			1 x 22 l/mn¹
	Max pressure		175 bar	150 bar
	Main valve Std type		4 ways	2 ways
	Oil cooler		Air	Air
	Tipping system		Hydraulic	Hydraulic
Tracks	Standard track width		180 mm	180 mm
	Track rollers		4	3
	Rocking rollers		Yes	Yes
	Track tensioning		Yes	Yes
Performance and dimensions	Max. travel speed		0 – 3.6 km/h	0 – 4.8 km/h
	Operating load		600 kg	800 kg
	Weight without self-loading	Standard version	415 kg	500 kg
		High-tip version	535 kg	600 kg
	Weight with self-loading	Standard version		580 kg
		High-tip version		670 kg
	Length	Without self-loading	1,680 mm	1,940 mm
		With self-loading		2,530 mm
	Width	Without self-loading	695 mm	800 mm
		With self-loading		850 mm
	Height		1,155 mm	1,140 / 1,250 mm
	Dumping height		400 / 1,675 mm	450 / 1,440 mm
	Tip			1,150 x 800 x 350 mm

¹ In option

Powered by **YANMAR**









 $Printed in France-Materials \ and \ specifications \ are \ subject to \ change \ from \ the \ manufacturer \ without \ notice-Please \ contact \ your \ local \ Yanmar \ Construction \ Equipment \ Europe \ dealer \ for \ further \ information.$

Yanmar Construction Equipment Europe S.A.S.

25, rue de la Tambourine 52100 SAINT DIZIER – FRANCE contact@yanmar.fr

www.yanmar.eu